






















	Description	Tufted multi-height loop pile carpet tile	
	Dimensions	50cm x 50cm	
	Total thickness	7.1mm ± 10%	
	Pile height	4.0mm ± 0.5mm	
	Collection size	12 colourways, 4m ² per box	
	Commercial use	EN ISO 10874	Class 33, Suitable for any type of heavy contract application
	Pile composition	100% Invista Antron® Lumena polyamide 6.6	
	Dye method	100% solution dyed	
	Stitch density	208,032 per m ² ± 10%	
	Pile weight	978 gsm ± 10%	
	Total weight	4,493 gsm ± 10%	
	Primary backing	Polyester	
	Secondary backing	ProBac recycled mineral filler with low amount of modified bitumen and polyester fleece. Contains over 76% recycled content	
	Acoustic	ISO 10140-3	Impact sound $\Delta L_W = 26$ dB
		ISO 354	Sound absorption = 0.15
	Castor chair use	ISO 4918	r ≥ 2.4 continuous use
	Light fastness	EN ISO 105-B02	≥ 5
	Dimensional stability	EN 986	≤ 0.4%
	Creating Better Environments	Renewable Energy	All Tessera carpet tiles are manufactured using 100% renewable energy (electricity & biogas)
		Recycled Content	Earthscape carpet tiles contain 57% recycled content by weight
	Indoor air quality	Earthscape carpet tiles products comply to 01350 Indoor Air Quality Standard	
	Back to the Floor	Installation off cuts can be collected via Back to the Floor	
	Ska rating	Earthscape meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes	
	Prodis-GUT	www.pro-dis.info	3140E7F6
	Installation method	Monolithic or quarter turn	
Earthscape carpet tiles meet the requirements of EN 14041			
	Product code	EN 14041	1170100-DoP-306
	Reaction to fire	EN 13501-1	B _{f1} -s1, G, NCS
	Slip resistance	EN 13893	μ ≥ 0.30
	Body voltage	ISO 6356	< 2.0kV
	Thermal resistance	ISO 8302	0.079 m ² .K/W

Office - Showroom

T: +90 212 274 44 22 | +90 212 274 42 89

E: info@anilzemin.com | bilgi@anilzemin.com Web: www.anilzemin.com

A: Vadi İstanbul Bulvar 2A Ofis | Ayazağa Mah. Cendere Cad. No: 109 / I Daire: 15-16 Sarıyer / İST

logistics 1

T: +90 212 229 44 38 | E: info@anilzemin.com | bilgi@anilzemin.com | www.anilzemin.com A: Poligon Mah. Sevim Sok. No:10/B İstinye / Sarıyer / İstanbul

logistics 2

Hellmann Worldwide Logistics

Samples:

Tel: 0212 274 44 22

E mail: info@anilzemin.com