

















# Technical specifications




**tessera**<sup>®</sup> mix

Mix carpet tiles meet the requirements of EN 1307

Description		Tufted multi-height loop pile carpet tile, Random lay. batchless
	Dimensions	50cm x 50cm
	Total thickness	5.9mm ± 10%
	Pile height	3.0mm ± 0.5mm
	Collection size	15 colourways, 5m <sup>2</sup> per box
	Application	EN 1307 Class 33, Suitable for any type of heavy contract application
	Pile composition	100% Invista Antron <sup>®</sup> Lumena polyamide
	Dye method	100% solution dyed
	Stitch density	200,600 per m <sup>2</sup> ± 10%
	Pile weight	650 gsm ± 10%
	Total weight	4,165 gsm ± 10%
	Primary backing	Polyester
	Secondary backing	Modified bitumen and polyester fleece
	Castor chair use	BS EN 985 Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02 ≥5
	Dimensional stability	BS EN 986 ≤0.2%
	Creating Better Environments	
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources
	Recycled Content	Mix contains over 50% recycled content by weight
	Indoor Air Quality	Mix meets 01350 Indoor Air Quality standard
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor
	Ska	Mix meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes
	Guarantee	Mix carpet tiles are guaranteed for 10 years under heavy contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
	Installation method	Random

Mix carpet tiles meet the requirements of EN 14041

**CE**  
EN 14041

	Reaction to fire	EN 13501-1	B <sub>f1</sub> -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 <sup>9</sup> Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

**BREEAM ratings**

Tessera Mix – Carpet Tiles (EN1307)

Building Type	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
Office	A	A	B	A	A+	✓