


















Technical specifications




Highlands

Highlands carpet tiles meet the requirements of EN 1307

	Description	Tufted multi-height loop pile carpet tile	
	Dimensions	50cm x 50cm	
	Total thickness	6.5mm ± 10%	
	Pile height	3.9mm ± 0.5mm	
	Collection size	6 colourways, 4m ² per box	
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition	100% polyamide 6	
	Dye method	100% solution dyed	
	Stitch density	198,374 per m ² ± 10%	
	Pile weight	605 gsm ± 10%	
	Total weight	4,120 gsm ± 10%	
	Primary backing	Polyester/Nylon	
	Secondary backing	Modified bitumen and polyester fleece. Also available in SOFTbac® secondary backing	
	Acoustical impact noise reduction	EN ISO 717-2 / ISO 10140-3	25 dB
	Castor chair use	EN 985	Minimum R value: ≥ 2.4
	Light fastness	EN ISO 105 B02	≥ 5
	Dimensional stability	EN 986	≤ 0.2%
	Creating Better Environments		
	Renewable Electricity	All carpet tiles are manufactured using 100% electricity made from renewable sources	
	Recycled Content	Highlands contains over 50% recycled content by weight	
	Indoor Air Quality	Highlands meets 01350 Indoor Air Quality standard	
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor	
	Ska	Highlands meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes	
	Guarantee	Highlands carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac®) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
	Installation method	Monolithic, quarter turn or tessellated	

Highlands carpet tiles meet the requirements of EN 14041



	Reaction to fire	EN 13501-1	B _{fl} -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	EN 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings

Highlands – Carpet Tiles (EN1307)

Building Type	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
Office	A	A	B	A	A+	✓

Our recommended adhesive for our collection of **AZM Carpet Int.** carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All **AZM Carpet Int.**' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All **AZM Carpet Int.**' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Highlands carpet tiles are manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of **AZM Carpet Int.**' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

AZM Carpet Int. carpet tiles are manufactured in UK

Kore Şehitleri Cad. Yüzbaşı Kaya Aldoğan Sok. No:3 Daire:7-8 Kat:1
34394 Zincirlikuyu / Şişli / İSTANBUL
Tel: +90 212 274 44 22 -0212 274 42 89 -0212 274 42 90
Fax:+90 212 274 42 80
Email: info@anilzemin.com
www.anilzemin.com

